



PX Electronics Limited

Tel: +44 0118 206 7525

Email: info@pxelectronic.com

Website: <https://www.pxelectronic.com/>

Specification – PXe Series Static Frequency Converter	
Model	PXe-330100F
Capacity	100kVA
Phase	Three Phase
Input	
Nominal Voltage	220V (L-N)/ 380V (L-L) $\pm 10\%$, 3 Phase +G +N
Acceptable Range	342-418V (L-L)
Frequency	50Hz ± 5 Hz
Power Factor	> 0.8 (Standard)/ >0.9 (Optional type, 12 pulse)
Output	
Nominal Voltage	220V (L-N)/ 380V (L-L) $\pm 10\%$, 3 Phase +G +N
Rated Current	151A per phase @ 220V
Frequency	400Hz $\pm 1\%$
Voltage Accuracy	< $\pm 1\%$ FS (Full Scale)
Frequency Accuracy	< $\pm 0.1\%$ FS (Full Scale)
Total Harmonic Distortion (THD)	THD < 3% @ Linear Load, pure sine wave output
Crest Factor	1.414
Overload Capacity	100% continuous, <110% - 15 minutes, <125% - 10 minutes, <150% - 1 minute, <200% - 5 seconds >200% output cut off
Interface	None for standard units RS232C/ RS485/ GPIB (Optional)
Protection	Over Current, Over Load, Over Voltage, Over Heat, Short Circuit, Alarm and Indicators
Enclosure IP	IP20
LED/ LCD Display	Digital Frequency Meter Digital Voltage Meter Digital Current Meter Digital Power/ PF Meter
Connectors	Hard-Wire Terminals, EN60309, MIL-STD, or client choice
Environment	
Temperature	Operational: -10C~55C Ambient: -10C~45C
Noise	<65dB at 1 meter, EN55022, IEC1000-4

Humidity	10~90% non condensing
Cooling	Variable speed fan, air intake in base, exhaust at rear
Altitude	<3000 meters
Castors or Feet	4kVA+ have castors with front brakes. A/Vs or feet optional
Reliability & Efficiency	
Mean Time Between Failure (MTBF)	50,000Hrs
Mean Time to Restore (MTTR)	<30 minutes
Overall Efficiency	➤ 85%
Dimensions and Weight	
Dimensions	1000x700x1450mm
Weight	600kg
Standards	
CE	CE Marked, UL Conforming
GB 50054-95, GB 50150-1991, GB 50150-2006, GB 50171-1992, GB/T 16935.5-2008, GB/T 16935.4-2011	
EN IEC61000-3-2, EN 6100-3-3, EN55032, EN55035, MIL-STD 461, MIL-STD 704, STANGAG 1008	

